



# SSP

Safety System Products

## S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

### Safety Simplifier | for HOLDX R1

#### Your advantages

- 14 I/O's as safety inputs or redundant OSSD-outputs
- wireless interface for safe communication, programming & diagnosis
- IP65
- 40mm width for aluminium safety fence systems



To the downloads ►

we simplify safety



## Safety System Products

# S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

With the Safety Simplifier we take safety where it is needed and we provide safety where it is needed with the Safety Simplifier and make it easier for you to develop user-friendly safety systems, such as on access doors. Simply connect up your sensors, locking systems or light curtains. Select the required push button and/or emergency stop button and you have a complete safety solution with analysis and diagnosis functions. This data is wirelessly transmitted via another Safety Simplifier or directly transmitted to your existing system in a fail-safe manner.

### General data

Type designation	S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07
Item number	SP-X-89-000-47
Functional type	safety PLC with safe wireless interface, internal antenna

### Button position 1

Type designation	E2
Function type	Emergency- Stop- Button

### Button position 2

Type designation	I1
Function type	Illuminated Button

### Button position 3

Type designation	I1
Function type	Illuminated Button
Colour	red, yellow, green, blue, white

### Connection

- Position 3	Q3C- male connector M12 5-Pin
- Position 4	Q4I - female connector M12 8-Pin

### Safety data

#### CPU

- EN ISO 13849-1: 2008	Category 4
- IEC 61508-2	SIL CL 3



## Safety System Products

### S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

- EN 62061 PFHD [1/h]	□
- EN ISO 13849-1: 2008 TM [Year]	20

#### 1-channel input

- EN ISO 13849-1: 2008	Category 2
- IEC 61508-2	SIL CL 2
- EN 62061 PFHD [1/h]	□
- EN ISO 13849-1: 2008 TM [Year]	20

#### 2-channel input

- EN ISO 13849-1: 2008	Category 4
- IEC 61508-2	SIL CL 3
- EN 62061 PFHD [1/h]	□
- EN ISO 13849-1: 2008 TM [Year]	20

#### 1-channel OSSD output

- EN ISO 13849-1: 2008	Category 2
- IEC 61508-2	SIL CL 2
- EN 62061 PFHD [1/h]	□
- EN ISO 13849-1: 2008 TM [Year]	20

#### 2- channel OSSD Output

- EN ISO 13849-1: 2008	Category 4
- IEC 61508-2	SIL CL 3
- EN 62061 PFHD [1/h]	□
- EN ISO 13849-1: 2008 TM [Year]	20

#### 2- channel relais output

- EN ISO 13849-1: 2008	Category 4
- EN 62061 SIL CIL	SIL CL 3
- EN 62061 PFHD [1/h]	□
- EN ISO 13849-1: 2008 TM [Year]	20

Approvals	CE, TÜV
-----------	---------

#### Environmental conditions

Max. storage temperature	-20°C +65 °C
Max. operating temperature	-20°C ... +65 °C

#### Electrical data

#### Technical data wireless safety



## Safety System Products

### S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

- max. amount of safe wireless channels 16

#### Channels

- Channel 1 2405 MHz

- Channel 2 2410 MHz

- Channel 3 2415 MHz

- Channel 4 2420 MHz

- Channel 5 2425 MHz

- Channel 6 2430 MHz

- Channel 7 2435 MHz

- Channel 8 2440 MHz

- Channel 9 2445 MHz

- Channel 11 2455 MHz

- Channel 10 2450 MHz

- Channel 12 2460 MHz

- Channel 13 2465 MHz

- Channel 14 2470 MHz

- Channel 15 2475 MHz

- Channel 16 2480 MHz

- amount of clamps 32

Supply voltage 10 - 30 V

Current consumption 110 mA with LED display

#### Conductor cross section

- single wire 0,08 ... 0,5 mm<sup>2</sup>

- fine wire 0,08 ... 0,5 mm<sup>2</sup>

- fine wired (wire sleeve without plastic collar) 0,25 mm<sup>2</sup>

stripping length 5-6 mm

#### configurable In-/ Outputs

14 semiconductor In-/ Outputs with help of software configurable □

Amount of safe inputs max. 14

Amount of safe semi-conductors OSSD outputs max. 14

Amount of semi-conductors auxilliary outputs max. 14

Amount of semi-conductors clock outputs max. 8

### S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

Input current	HIGH 2,4 mA ... 3,8 mA    LOW -2,5 mA ... 2,1 mA
Output type	PNP- Semiconductor
Output voltage	Operating voltage UB -0,5 V
Seperate output current	max. 0,6 mA (bei UB 24 V)
Total output current	max. 2 A (bei UB 24 V)

#### Button position 1

Type designation	E2
Function type	Emergency- Stop- Button
Switch type	2 Openers + LED
Bounce time NO	<10 ms
Bounce time NC	<10 ms
Break contact force opening	according to EN60947-5-1 Anh-K.
Illumination	LED
mechanical lifespan	50.000 switching cycles
electrical lifespan	50.000 switching cycles
B10d- Value	250.000

#### Button position 2

Type designation	I1
Function type	Illuminated Button
Switch type	1 closing device + LED
Bounce time NO	<10 ms
Bounce time NC	<10 ms
Break contact force opening	according to EN60947-5-1 Anh-K
Illumination	LED
mechanical lifespan	30.000 switching cycles
electrical lifespan	30.000 switching cycles

#### Button position 3

Type designation	I1
Function type	Illuminated Button
Colour	red, yellow, green, blue, white
Switch type	1 closing device + LED
Bounce time NO	<10 ms
Bounce time NC	<10 ms



## Safety System Products

### S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

Break contact force opening	accordint to EN60947-5-1 Anh-K
Illumination	LED
mechanical lifespan	30.000 switching cycles
electrical lifespan	30.000 switching cycles

#### General data

Memory card	Installation of a memory card MEM-SP-N-88-001-93 possible
Type terminal connection	clamp terminal
- fine wired (wire sleeve with plastic collar)	0,08 ... 0,5 mm <sup>2</sup>
Input voltage	HIGH 75% from UB (adjustable by software) LOW 25% from UB (adjustable by software)

#### Technical data inputs

#### Technical data safe OSSD outputs, auxilliary and test pulse outputs

Short-circuit proof	Yes
---------------------	-----

#### Mechanical data

Installation opening of buttons	22,5 mm
Type of housing	H09


#### Dimensions

Height	44 mm
Length	253 mm
Width	42 mm

### S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

#### Electrical drawings

#### Connection example 1










#### Equipment

#### Wireless Safety









Article code ZTK5	Button cap set for illuminated buttons	SP-X-88-001-19	
	Inscription label set ZB1	SP-X-88-001-21	

## S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

	Inscription label set ZB2	SP-X-88-001-22	
	Inscription label set ZB3	SP-X-88-001-23	
	Inscription label set ZB4	SP-X-88-001-93	
Article code ZMT	Installation wrench	SP-X-88-001-25	
Article code ZUK	Liftingtool for button and light caps	SP-X-88-001-26	
Article code ZMB	Mounting plate big	SP-N-88-850-02	
Article code ZMS	Mountingplate small	SP-N-88-850-01	



## S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

Article code ZSD	Screw with seal	SP-X-88-001-89	
External antenna for Safety Simplifier, cable length 1 m	Simplifier EXTA 1 m	SP-X-88-200-24	
External antenna for Safety Simplifier, cable length 10 m	Simplifier EXTA 10 m	SP-X-88-200-20	
External antenna for Safety Simplifier, cable length 2 m	Simplifier EXTA 2 m	SP-X-88-200-23	
External antenna for Safety Simplifier, cable length 5 m	Simplifier EXTA 5 m	SP-X-88-200-22	
External antenna for Safety Simplifier, cable length 8 m	Simplifier EXTA 8 m	SP-X-88-200-21	
Free software for the Safety Simplifier System	Simplifier Manager		
	Simplifier Monitor SRM	SP-N-88-850-03	

## S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

Fastening set for Safety Simplifier for back panel  
mounting

Simplifier ZHMS

SP-X-88-001-91



Fastening set for Safety Simplifier

Simplifier ZHS

SP-X-88-001-91



### Safety switches

Magnetic process lock

HOLDX S1

SP-X-73-001-10



### Accessories

M12-female connector, 12 pin, 10 m

M12-C12101-G

SP-X-33-000-21



M12-female connector, 12 pin, 20 m

M12-C12201-G

SP-X-33-000-22



M12-female connector, 5-pin

M12-C51-G

SP-X-33-001-00



M12-male connector, 5 pin

M12-C52-G

SP-X-33-001-01



M12-female connector, 8 pin

M12-C81-G

SP-X-33-001-02



## S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07

M12-male connector, 8 pin

M12-C82-G

SP-X-33-001-03



M12-connecting cable, 12 pin, 1 m

M12-M12-C1213-G

SP-X-33-000-30



M12-connecting cable, 5 pin, 0,5 m

M12-M12-C5023-G

SP-X-33-000-10



M12-connecting cable, 5 pin, 1 m

M12-M12-C513-G

SP-X-33-000-11



M12-connecting cable, 5 pin, 2 m

M12-M12-C523-G

SP-X-33-000-12



M12-connecting cable, 8 pin, 10 m

M12-M12-C8103-G

SP-X-33-000-09



M12-connecting cable, 8 pin, 1 m

M12-M12-C813-G

SP-X-33-000-25



### Operating elements

Universal hook

SP UH-K





**Safety System Products**

## **S14LDRB-H09-E2-I1-I1-Q1A0-Q2A0-Q3C0-Q4I0-W07**

### **Downloads**

- Certificates
- STEP
- Product line
- Catalog
- Certificates
- Catalog packaging systems
- Operating manual
- EPLAN-Data